REDSOLAR

M10-MBB TOPCon Mono Bifacial Module

(156Half Cells)



12 years Product warranty

30 years Linear power warranty

Integrated Solar Manufacturing & Technology Since 1964

605-625W /Output power

22.4% /Maximum efficiency

0~+5W /Power tolerance

PID Resistant

Strict selection of encapsulation materials eliminates PID risk.

Better Performance

30-year linear warranty, 1% decline in the first year an average annual decline of 0.40% over the first 30 years, increased returnon investment No Boron-oxygen LID (Light Induced Degradation).

High Returns

The n-type module has lower annual attenuation, better photoelectric conversion efficiency and temperature coefficient benefit, bifaciality can reach 80%.

Multi Busbar Technology

Better light utilization and current collection ability, effectively improve the power output and reliability.

Comprehensive product certification

- IEC 61215 IEC61730
- IEC TS 62804 (PID Resistant)
- IEC 62716 (Ammonia Corrosion)
- IEC 61701 (Salt Spray Corrosion)
- IEC TS 62941 (PV quality Management System)
- ISO9001：2015 (Quality Management System)
- ISO14001 (Environmental Management System)
- OHSAS18001 (Occupational Health and Safety Management System)

Excellent Power Guarantee



Hunan Red Solar New Energy Science and Technology Co.,Ltd

www.red-solar.com

sales@red-solar.com

REDSOLAR

M10-MBB TOPCon Mono Bifacial Module

Model of PV Module

CETC-xxxT(GDF)/156

Power Range

605-625W

PV module dimensions (mm)



P-V Curves of PV Module



I-V Curves of PV Module



Electrical Parameter(STC)

Model	605T	610T	615T	620T	625T
Maximum power (W)	605	610	615	620	625
Working point voltage (V)	45.80	45.90	46.10	46.20	46.30
Working point current (A)	13.22	13.29	13.35	13.42	13.50
Open circuit voltage (V)	54.8	54.9	55.1	55.2	55.3
Short circuit current (A)	13.97	14.04	14.10	14.17	14.25
PV module efficiency	21.64%	21.82%	22.00%	22.18%	22.36%
Standard test conditions	AM1.5, Irradiance 1000w/㎡, Cell Temperature 25°C				

RearSide Power gain

5%	Maximum Power	635Wp	641Wp	646Wp	651Wp	656Wp
	Efficiency STC	22.75%	22.93%	23.12%	23.31%	23.50%
15%	Maximum Power	696Wp	702Wp	707Wp	713Wp	719Wp
	Efficiency STC	24.91%	25.12%	25.32%	25.53%	25.74%
25%	Maximum Power	756Wp	762Wp	769Wp	775Wp	781Wp
	Efficiency STC	27.08%	27.30%	27.53%	27.75%	27.97%

The Electrical performance parameters are neither just referred to one PV panel, nor are a part of the contract; They are only used as reference.

Mechanical Parameters

Module size	2465*1134*30mm
Number of solar cells	156Cells (2*6*13)
Weight	33.2Kg ±5%
Junction Box	IP68, 3 diodes
Cables	4mm², +:300mm/ -:200mm (Customizable)
Front plate glass	2.0mm,Ultra white AR coated semi-toughened glass
Rear plate glass	2.0mm, semi-toughened glass
Static load on the front	5400Pa
Static load on the back	2400Pa

Packaging&Transport

40'HQ container transport	36 Pcs/box × 16box = 576 Pcs

Temperature Parameter

NMOT	42±2°C
Temperature coefficient of maximum power(Pmax)	-0.30%/°C
Temperature coefficient of open circuit voltage(Voc)	-0.25%/°C
Temperature coefficient of short circuit current(Isc)	+0.045%/°C

Maximum Ratings

Working temperature	-40~+85°C
Maximum system voltage	1500VDC
Maximum fuse rated current	30A

All data contained in this specification are subject to change without prior notice. The final interpretation rights belong to Hunan Red Solar New Energy Science and Technology Co.,Ltd (2023088V03)